



US005128981A

United States Patent [19][11] **Patent Number:** **5,128,981****Tsukamoto et al.**[45] **Date of Patent:** **Jul. 7, 1992****[54] RADIO COMMUNICATION SYSTEM AND A PORTABLE WIRELESS TERMINAL**

[75] Inventors: Nobuo Tsukamoto, Tachikawa;
Hiroshi Kuwahara, Kodaira; Yuji
Sakamoto, Kokubunji; Kumiko
Takikawa, Tama, all of Japan

[73] Assignee: Hitachi, Ltd., Tokyo, Japan

[21] Appl. No.: 526,246

[22] Filed: May 21, 1990

[30] Foreign Application Priority Data

May 24, 1989 [JP] Japan 1-128824
May 26, 1989 [JP] Japan 1-131352

[51] Int. Cl.: **H04M 11/00**

[52] U.S. Cl.: **379/58; 379/59;**
379/60; 379/61; 379/63

[58] Field of Search 370/62, 108, 110.1;
379/56, 57, 58, 59, 60, 61, 62, 63, 112; 455/33

[56] References Cited**U.S. PATENT DOCUMENTS**

4,312,074	1/1982	Pautler et al.	375/96
4,456,793	6/1984	Baker et al.	379/56
4,481,382	11/1984	Villa-Real	379/61
4,661,659	4/1987	Nishimura	379/61
4,771,448	9/1988	Koohgoli et al.	379/60
4,843,622	6/1989	Yotsutani et al.	379/59
4,852,148	7/1989	Shibata et al.	379/59
4,914,686	4/1990	Hagar, III et al.	379/61
4,972,457	11/1990	O'Sullivan	379/59
4,980,907	12/1990	Raith et al.	379/63

FOREIGN PATENT DOCUMENTS

0344989	12/1989	European Pat. Off.	379/59
62-143171	6/1987	Japan	
0001226	3/1989	Japan	379/59
86/00775	1/1986	World Int. Prop. O.	379/60

OTHER PUBLICATIONS

Akio Sasaki et al., "System Configuration of Multi-Zone Cordless Telephone", NIT Electrical Communications Laboratories, The Institute of Electronics and Communication Engineers of Japan 1986 All Japan Meeting, No. 438, pp. 2-256. Provided in Japanese. An English translation is unavailable to applicants' attorney.

Cardona, Heim and Turriere "Digital Data Transmission System for Fixed and Mobile Subscribers", Electrical Communication vol. 52, #3, 1977.

Primary Examiner—James L. Dwyer

Assistant Examiner—William Cumming

Attorney, Agent, or Firm—Fay, Sharpe, Beall, Fagan, Minnich & McKee

[57] ABSTRACT

This invention proposes a radio communication system including a plurality of radio terminals, a relay apparatus (including a plurality of base stations and an exchange station) connected to each radio terminal so that the radio terminals can interchange information from each other, and a data processing unit connected to the relay apparatus, each radio terminal having a circuit for inputting and outputting a voice signal and a circuit for inputting and outputting data whereby it can communicate with another radio terminals or with the data processing unit through the relay apparatus. The radio terminal of this invention further has a clock, and a circuit for storing a schedule inputted by the user thereby to automatically select a receiving mode such as a ringing mode or a nonringing mode in accordance with the contents of the schedule, the present time and so on.

16 Claims, 20 Drawing Sheets